

Occupancy Indicator Deadbolt Model No. TD-100





Application

For the restroom doors in residential and commercial buildings such as apartment, airport, educational or governmental facilities etc..

Description

- •TD-100 is a commercial restroom indicator deadbolt which is UL 10C compliant.
- Occupancy indicator, read either "IN USE" or "VACANT" with color coding, is outside.
- Bolt automatically deadlocks when fully throw.

Features

- Thumbturn is large and easy to use.
- Non-handed. It may be used on right hand or left hand doors swinging in or out.
- Tapered front housing that can't be unscrewed
- Anti-Microbial coating is available on request
- Emergency key is supplied on request. It can unlock the deadbolt from outside.
- Adjustable backset

Certifications

UL listed, conform to UL 10C Standard.
 A label, 3-Hour Fire Rating

Specifications

 \bullet Door thickness: 1-3/4" $^{\sim}$ 2" (44.5~51mm)

• Latch Bolt projected Length: 1" (25.5mm)

• Latch type: Square Corner

• Latch material: Stainless steel

 Exposed Trim: Stainless steel reinforced with plated steel insert

• Backset: Furnished standard with 2-3/8" (60mm) or 2-3/4" (70mm)

• Faceplate: 1" x 2-1/4" (25.5mm x 57mm)

• **Strike**: 1-3/16" x 2-1/4" (30mm x 57mm)

• Screws: Furnished with wood/machine screws for use on wood or metal doors or frame.

Finishes

US26D, US32D