

## STRIKES

### FOR HEAVY DUTY EXIT DEVICES (SCREWS INCLUDED)

#### RIM DEVICE USE

##### Rim Strikes



**801**

Standard for  
8510S/8710S  
8610S/8810S

Projection: 13/16" (21mm)




**802**

Standard for  
8510F/8710F  
8610F/8810F

Projection: 13/16" (21mm)

##### Mullion Strike



**688**  
Strike

**689**  
Hook

Projection: 7/8" (22.5mm)

Standard for  
panic rated  
mullion 7200,  
LBR8630S  
LBR8830S

##### Top Strikes



**812**

Standard top  
strike for  
8530S/8730S  
8630S/8830S

Projection: 29/32" (23mm)



**822**

Standard top  
strike for  
8530F/8730F  
8630F/8830F

Projection: 1-1/8" (29mm)

##### Bottom Strikes (Floor Strikes)



**815**

Standard floor  
strike for  
8530S/8730S  
8630S/8830S  
8550S/8750S  
8650S/8850S



**825**

Standard floor  
strike for  
8530F/8730F  
8630F/8830F  
8550F/8750F  
8650F/8850F

Mortise: 2-1/4" (57mm)

##### Threshold Strikes




**862**

Optional floor strike  
for using threshold  
openings

Projection: 6/16" (9.5mm)

#### MORTISE DEVICE USE

##### Mortise Strikes



**818**



**828**

For use on 1-3/4"  
standard or 2-1/4"  
thick single door,  
and 2-1/4" double  
door with over-  
lapping astragal  
and coordinator

818: Standard for  
8620S/8820S

828: Standard for  
8620F/8820F

##### Double Door Strikes



**720**

Not included  
with device,  
sold separately

Projection: 1-15/16" (33mm)

##### Sex Nuts and Bolts (SNB)



**618** SNB – 1-3/4" thick door use  
(Standard door)

**623** SNB – 2-1/4" thick door use

**630** SNB – 2-1/2" thick door use

#### OTHERS