

WIDE STILE EXIT DEVICES

RIM EXIT DEVICE

*A highly popular single-point lock
for single swing exit door use*



Certifications

- ANSI A156.3 - 2020 Grade 1
- UL/cUL listed, UL listed as:
 - Panic Exit Hardware
 - 3-hour Fire Exit Hardware

Model No. 8610 & 8810

- 8610S/8810S : Panic-Rated Rim Exit Device
- 8610F/8810F : Fire-Rated Rim Exit Device

Applications

- Suitable for all types of single and double doors with mullion.
- Fire-rated devices are for UL listed fire-labeled single doors up to 4'x8' (1219mm x 2438mm) or 8'x8' (2438mm x 2438mm) double doors with mullion.

Dogging Options

- RD – Standard dogging
- LD – Less dogging
- CD – Cylinder dogging
- HD – Head dogging (See page 30)

Quiet Solution (Optional)

Specify "Quiet Solution" when ordering.

Finishes

US3, US4, US10, US10B, US15, US26, US26D, US32D

Specifications

Device Lengths	Short (36"): 33-5/32" (842mm) Long (48") : 45-1/8" (1146mm)
Door Widths	36" - For 29" to 36" (736mm to 914mm) door size 48" - For 33" to 48" (838mm to 1219mm) door size
Minimum Stile Width	4-1/4" (107mm)
Latch Bolt	3/4" (19mm) throw, deadlocking design
Strikes	801 (panic), 802(fire)
Dogging Kit	Panic device - Hex key dogging standard (RD) Fire device - No mechanical dogging (ND)
Dogging Options	Cylinder Dogging (CD), Less Dogging (LD) Head Dogging (HD) optional for electrified panic-rated devices
Mounting Fasteners	Panic device - Machine screws furnished as standard Fire device - Sex nuts and bolts (SNB) supplied as standard For wood doors - SNB are required; order SNB separately
Mounting Height	From finished floor to device centerline – 40 inches (1016mm) standard