

NARROW STILE EXIT DEVICES

RIM EXIT DEVICE



Certifications

- ANSI A156.3 - 2020 Grade 1
- UL/cUL listed, UL listed as:
 - Panic Exit Hardware
 - 3-hour Fire Exit Hardware

Model No. 8510 & 8710

- 8510S/8710S : Panic-Rated Rim Exit Device
- 8510F/8710F : Fire-Rated Rim Exit Device

Applications

- Panic-rated narrow stile devices are used for aluminum frame full glass doors or narrow stile aluminum door applications.
- Fire-rated narrow stile devices are used for aesthetic requirements on single doors up to 4'x8' (1219mm x 2438mm) or double metal or wood doors up to 8'x8' (2438mm x 2438mm) with mullion.

Quiet Solution (Optional)

Specify "Quiet Solution" when ordering.

Finishes

US3, US4, US10, US10B, US15, US26, US26D, US32D

Specifications

Device Lengths	Short (36"): 34-11/32" (872mm) ; Long (48"): 46-5/16" (1176mm)
Door Widths	36" - For 29" to 36" (736mm to 914mm) door size 48" - For 33" to 48" (838mm to 1219mm) door size
Minimum Stile Width	2-19/32" (66mm)
Latch Bolt	3/4" (19mm) throw, deadlocking design
Strikes	801 (panic), 802(fire)
Dogging Kit	Panic device - Hex key dogging standard (RD) Fire device - No mechanical dogging (ND)
Dogging Options	Cylinder Dogging (CD), Less Dogging (LD)
Mounting Fasteners	Panic device - Machine screws furnished as standard Optional SNB are available for the device, but must be ordered separately Fire device - Sex nuts and bolts (SNB) supplied as standard
Mounting Height	From finished floor to device centerline – 40 inches (1016mm) standard