

## NARROW STILE EXIT DEVICES

### SURFACE VERTICAL ROD EXIT DEVICE



#### Model No. 8530 & 8730

- 8530S/8730S : Panic-Rated SVR Exit Device
- 8530F/8730F : Fire-Rated SVR Exit Device

#### Applications

- Narrow design panic exit devices are used for full glass aluminum doors or narrow stile aluminum door applications.
- Narrow design fire-rated devices are used for pairs of wide stile metal or wood doors up to 8'x8' (2438mm x 2438mm) where aesthetic requirements are important.

#### Quiet Solution (Optional)

Specify "Quiet Solution" when ordering.

#### Finishes

US3, US4, US10, US10B, US15, US26, US26D, US32D

#### Certifications

- ANSI A156.3 - 2020 Grade 1
- UL/cUL listed, UL listed as: Panic Exit Hardware or 3-hour Fire Exit Hardware

## Specifications

Device Lengths	Short (36"): 34-11/32" (872mm) ; Long (48"): 46-5/16" (1176mm)
Door Widths	36" - For 29" to 36" (736mm to 914mm) door size 48" - For 33" to 48" (838mm to 1219mm) door size
Minimum Stile Width	2-19/32" (66mm)
Latch Bolts	Top latch 5/8" (16mm) throw, can be automatically deadlocked Bottom latch 5/8" (16mm) throw, held in retracted position during door swing
Strikes	Top - 812 (panic), 822 (fire); Bottom - 815 (panic), 825 (fire)
Dogging Kit	Panic device - Hex key dogging standard (RD) Fire device - No mechanical dogging (ND)
Dogging Options	Cylinder Dogging (CD), Less Dogging (LD)
Mounting Fasteners	Panic device - Machine screws furnished as standard SNB furnished for the top & bottom latches Optional SNB available for the device, but must be ordered separately Fire device - Sex nuts and bolts (SNB) supplied as standard
Mounting Height	From finished floor to device centerline – 40 inches (1016mm) standard
Door Opening Height	Standard door height is 7 ft (2134mm), and 8 ft (2438mm) is also available For door heights exceeding 8', please specify when ordering
Vertical Rods	Rods - 1/2" (13mm) diameter tubular with guides Top rod - two pieces, fits 7' or 8' door heights Bottom rod - single piece, 31-1/4" (794mm) in length