

## AUXILIARY HARDWARE

### UNIVERSAL DOOR COORDINATOR

#### Model No. 7600



The 7600 Universal Door Coordinator is designed for pairs of doors up to 8' (2438mm) wide. It provides a smooth, quiet, and functional means of controlling the closing sequence of active and inactive doors.

The 7600 Universal Door Coordinator is widely used to control the closing cycles of door pairs where the active door may be equipped with or without an overlapping astragal, and the inactive door feature either a concealed vertical rod exit device or a pair of automatic flush bolts. This door coordinator prevents the active door from closing before the inactive door, helping both leaves avoid collision with each other.

#### Features:

- Non-handed design allows for flexible installation on either left or right-opening doors
- Simple and quick installation process reduces labor time and costs
- Door stop mounting eliminates the need for additional top mounting brackets
- Compatible with most standard door configurations

#### Product Information

Size	Length: 20" (508mm)
	Width: 1-18/32" (40mm)
	Thickness: 25/32" (20mm)
Material	Steel construction
Finishes	Premium powder coat finish available in:
	Gray
	Black powder coating
Certifications	UL/cUL listed. UL listed as 3-hour Fire Hardware
	Conforms to ANSI A156.3-2020 Grade 1, Type 21B

Note: Not for use with surface vertical rod panic devices.

